

MT-605.02 J

Rugged Handheld

MT-605.02 J



Windows



IP65



GPS



High-capacity



Bluetooth



Camera



2D



NFC



4G



WiFi



Functions

- Support for Windows 11/10 system
- Equipped with front 5 million and rear 8 million pixel auto focus camera
- Support 4G all network communication, Dual-band WiFi, Bluetooth and other communication modes
- Removable 7.4V 4000mAh high-voltage high-capacity battery, supports PD fast charging
- Support GPS, Glonass, more accurate positioning
- Support NFC and the optional 2D module , to meet the application needs of multiple industries
- IP65 high protection level, in accordance with MIL-STD-810H

Product Six Views








Specification Parameter

Basic parameters	
Dimension	183.1*88.6*24.1mm
Weight	Device unit 470g
Device Color	Black
LCD	6.5 inch TFT 20:9, 720*1600, 400cd/cm ²
Touch Panel	10 point G+FF capacitive touch screen Corning® Gorilla® Glass
Camera	Front 5.0MP Rear 8.0MP
I/O	TYPE-C 2.0*1 OTG (Data transmission) Standard USB-A port/Data Transfer (3.0) TF card *1, Max: 512GB Nano-SIM * 1 Pogo Pin (Suitable docking charger DC61J)
Power	PD Fast Charge Adapter
Communication	
WIFI	WIFI 802.11(a/b/g/n/ac) Dual frequency 2.4G+5.8G WIFI
Bluetooth	BT5.0 Transmission distance: greater than 10m
3G/4G	LTE FDD: B1/B3/B7/B8/B20 LTE TDD: B40 WCDMA: B1/B5/B8 GSM: 900/1800 Optional: LTE-FDD: B2/4/5/12/13/17/18/25/26 LTE-TDD: B41 WCDMA: B2/4/5 CDMA&EVDO: BC0/BC1 GSM: 850/1900 LTE-FDD: B2/4/5/7/8/28 LTE-TDD: B40 WCDMA: B2/5/8 GSM: 850/900/1900
GNSS	GPS+GLONASS

Performance parameter	
CPU	Intel JASPER LAKE N5100
OS	Windows 11/10
RAM	8GB
ROM	128GB
Battery	
Capacity	7.4V/4000mAh
Type	External polymer lithium ion battery
Endurance	About 6 hours(50% volume sounds, 50% screen brightness, 1080P HD video display by default)
Reliability	
Operate Temperature	-20 °C ~ 60 °C
Store Temperature	-30 °C ~ 70 °C
Humidity	95% Non-Condensing
Rugged Feature	IP65 certified, MIL-STD-810H certified
Drop Height	1.5m
Data Collection	
NFC	Support, 13.56MHz, Support ISO/IEC 14443A/14443B/15693/18092/ mifare protocol Card reading distance: 3-5cm
2D	Optional, Optical resolution: 5mil Scanning speed: 30 times/s Support code: PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, Maxicode, QR Code, MicroQR, QR Inverse, Aztec, Aztec Inverses, Han Xin, Han Xin Inverse

The Accessories

				
PD Fast charge adapter	Hand-strap	Docking charger DC61J	Vehicle Mount	TP Resist film
Standard	Standard	Optional	Optional	Support mass customization

All technical data, specifications and performance figures subject to change without prior notice.

BizTech Distribution GmbH | www.biztech-distribution.eu
Phone: +49 30 220121411 | E-Mail: contact@biztech-distribution.eu

biz/TECH
distribution