MT-606.3 M





Performance

- ·ARM Octa-core CPU with two Arm 'Big' Cores
- ·Android 12 OS and 4GB RAM+64GB storage
- $\cdot 5.99$ inch IPS screen with 5–point touch

Communication

- $\cdot \textsc{Dual}$ 5G (SA/NSA) network support
- ·Dual-band Wi-Fi 5
- $\cdot \text{Upgrade BT 5.1, fast and more stable}$

Function

- ·Professional 2D scanner an multi-function NFC
- $\cdot \text{Support GPS}$ / GLONASS / GALILEO / BDS
- $\cdot \ensuremath{\mathsf{Equipped}}$ with multiple accessories, like docking charger,
- hand-strap, hanging rope

Reliability

- ·IP65 Waterproof and Dustproof
- $\cdot \text{Impact}$ resistance: Drop from a height of 1.2 meters
- $\cdot \textsc{Built}$ to operate in extreme temperatures, MIL-STD-810H certified

NEC Read

Pogo Pin interfac

Product Six Views



Specification Parameter

Basic parameters		Performa
Dimension	164 x 80 x 14mm	CPU
Weight	255g	OS
Device Color	black	RAM
LCD	5.99 inch IPS 18:9, 720×1440	ROM
Touch Panel	5 point G+FF capacitive touch screen	Commun
Camera	Front 5.0MP Rear 13.0MP	WIFI
I/O	USB Type–C x 1, SIM Card, TF Card, Two out of three card holders (two nano SIM cards or	Bluetooth
	one nano SIM card and one TF card) Charge Pogo Pin x 1, Extend Pogo Pin x 1	2G/3G/4G/ (Optional)
Power	AC100V ~ 240V, 50Hz/60Hz, Output DC 5V/2A	
Battery		GNSS
Capacity	4500mAh/3.8V	
Туре	Removable polymer lithium ion battery	Reliabilit Operate
Endurance	8hrs (50% volume sounds, 200 lumens brightness, 1080P HD video display by default)	Temperatu
Data Collection		Temperatu
NFC	Built-in, 13.56MHz, Support ISO/IEC 14443A/B/15693/18092/mifare protocols Card reading distance: 4cm	Humidity Rugged Feature
2D	Support	Drop Heig
Fingerprint	Login fingerprint	

Performance parameter		
CPU	ARM (5G-C) (OCTA Core)	
OS	Android 12	
RAM	4GB	
ROM	64GB	
Communication		
WIFI	WiFi 802.11 a/b/g/n/ac (2.4G+5G)	
Bluetooth	BT5.1 Transmission distance: 10m	
2G/3G/4G/5G (Optional)	GSM: B2/B3/B5/B8 WCDMA: B1/B2/B5/B8 TDD: B38/B39/B40/B41 FDD: B1/B2/B3/B5/B7/B8/B20 5G: N1/N3/N5/N38/N41/N77/N78/N79	
GNSS	Support GPS+GLONASS+Beidou+Galileo	
Reliability		
Operate Temperature	–10 °C ~ 50 °C	
Store Temperature	–20 °C ∼ 60 °C	
Humidity	95% Non-Condensing	
Rugged Feature	IP65 certified, MIL-STD-810H certified	
Drop Height	1.2m	

Accessories









Docking Charger

Hand-strap

Lanyard

TP Resist film

Application Range

The handheld terminal with RFID UHF technology is widely used, which can meet the application in retail, storage material management, finance, express delivery, medical and other fields.







BizTech Distribution GmbH | www.biztech-distribution.eu Phone: +49 30 220121411 | E-Mail: contact@biztech-distribution.eu